





# AGEPAN® OSB 4 ECOBOARD

THE HIGH LOAD-BEARING BOARD







# AGEPAN® OSB 4 ECOBOARD

#### **ADVANTAGES**

- · Very high mechanical strength
- Formaldehyde-free and moisture-proof glued
- Reduced swelling and shrinkage
- Non-detrimental to health independent confirmation that it is safe to use with foodstuffs
- Suitable as an airtight level or vapour barrier
- High quality confirmed by regular, external inspections
- Raw material exclusively from responsible forest and timber industry

#### AREAS OF APPLICATION

- · Heavy-duty load-bearing OSB panel for the use in humid areas (utilization class 1 + 2)
- Wood-based panel type OSB/4 acc. to EN 300 or DIN EN 13986
- Structural heavy-duty wall elements and roof panelling
- Load-bearing ceiling sheathing
- Heavy-duty floor constructions
- · Housing, industrial and formwork construction

### **TECHNICAL DATA**

PROPERTY	UNIT	VALUE
Standard		EN 300 bzw. DIN EN 13986
Bulk density	kg / m³	≥ 610
Rated thermal conductivity $\lambda_{\scriptscriptstyle R}$	W / (m*K)	0,13
Water vapour diffusion resistance factor µ		200 / 250 (wet / dry)
Formaldehyde emission class		E1 – formaldehyde-free glued (< 0,03 ppm)
Fire classification		D-s2, d0
Thickness swelling in 24 h	%	12
Change in length per 1% change in moisture content	%	0,015

## CHARACTERISTIC VALUES acc. to EN 12369-1

Property Unit		Thickness	Bending f <sub>m</sub>		Tension f <sub>t</sub>		Compression f <sub>c</sub>		Panel shear f <sub>v</sub>	Panel shear f <sub>r</sub>
		(mm)	II or 0	I or 90	II or 0	I or 90	II or 0	I or 90		
Strength values N / mr		6 – 10	24,5	13,0	11,9	8,5	18,1	14,3	6,9	1,1
	N / mm²	> 10 – 18	23,0	12,2	11,4	8,2	17,6	14,0		
		> 18 – 25	21,0	11,4	10,9	8,0	17,0	13,7		
Property	Unit	Thickness	Bending E <sub>m</sub>		Tension E <sub>t</sub>		Compression E <sub>c</sub>		Panel shear G <sub>v</sub>	Panel shear G <sub>r</sub>
		(mm)	II or 0	I or 90	II or 0	I or 90	II or 0	I or 90		
Stiffness values	N / mm²	6 – 25	6.780	2.680	4.300	3.200	4.300	3.200	1.090	60





























www.pefc.org

Use products that are certified accordingly:  $FSC^{\circ}$ - and  $PEFC^{\circ}$ -certified products can be delivered on demand and within availabilities. Please specify when ordering.

Your AGEPAN® SYSTEM partner

