

Product Data Sheet

Dimensions	1900x 190x 15(4)mm
Pieces per pack	8
Overall thickness	15mm
m2 per pack	2,166m2
Percentage of short boards	18,80%
Package design	box/package with design

Construction	
Surface layer	Larch 4mm
Core layer	Pine 7mm
Back layer	Larch 4mm
T&G or click	T&G with bevel on 4sides
Moisture content	7% ± 2
Grading	AB
Finishing	Lacquered
Brand of lacquer	Treffert
Wear resistance	test result from factory Falling sand 2000 circles 175# sand paper
Stain resistance	test result from factory Class 5
Color of filler	Wood color

Installation	Floating or Glue down
---------------------	--------------------------

CE	EN 14342:2013
-----------	---------------

Aspect	
Lipping - differences in height	≤ 0.15mm
Difference in length	± 1.0mm
Difference in width	± 0.15mm
Cupping lengthwise	≤ 0.2%
Cupping in width	≤ 0.1%

Slip resistance	test result from factory	USRV 100
------------------------	--------------------------	----------

Emission of Formaldehyde	(EN 717-1)	≤ 0.124mg/m3 E1
---------------------------------	------------	--------------------

PCP	CEN/TR 14823	≤ 5ppm
------------	--------------	--------

Thermal conductivity	test result from factory	0.14 W/m2K
-----------------------------	--------------------------	------------

Biological Durability	(EN335-1)	Class 1
------------------------------	-----------	---------

Reaction to fire	(EN 13501-1)	Df1-s1
-------------------------	--------------	--------